


180° Pivot



- Pivots 180°, designed minimizes head room.
- Manufactured from forged alloy steel, quenched and tempered.
- Manufactured and tested in accordance with EN1677-1.
- Certified by DGUV GS-OA-15-04.
- Load rated parts are 100% magnaflux crack detected.
- Individual forged parts are traceable to Test Certification.
- Proof tested to 2.5 times the WLL.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- The two points of attachment facilitate an even and optimal force distribution into the work piece and thus, usage of thinner base plates is possible.
- The welding block is forged out of material with excellent welding properties.
- Low profile design with high strength.
- The ring is stowable thus avoiding the hazards of tripping and snagging.



Weld-on Ring

Metric (8-082)

Item No.	Working Load Limit	Dimensions (mm)										N.W.
	tonnes	A	B	C	D	E	F	L	M	HV	a	kg
8-082-04	4	66	14	30	48	65	70	135	76	5	3	0.6
8-082-06	6.7	85	20	39	60	89	91	171	98	5	3	1.5
8-082-10	10	95	21	46	65	100	100	196	106	7	4	2.4
8-082-16	16	127	30	57	90	130	136	263	149	8	4	5.5
8-082-30	31.5	178	42	78	130	160	160	375	213	15	4	15.8

* Design factor 4:1

Weld-on Ring

Imperial (8-082)

Item No.	Working Load Limit	Dimensions (inch)										N.W.
	tonnes	A	B	C	D	E	F	L	M	HV	a	lbs
8-082-04	4	2.6	0.55	1.18	1.89	2.56	2.76	5.31	2.99	0.2	0.1	1.3
8-082-06	6.7	3.35	0.79	1.54	2.36	3.5	3.58	6.73	3.86	0.2	0.1	3.3
8-082-10	10	3.74	0.83	1.81	2.56	3.94	3.94	7.72	4.17	0.28	0.2	5.3
8-082-16	16	5	1.18	2.24	3.54	5.12	5.35	10.35	5.87	0.31	0.2	12.1
8-082-30	31.5	7.01	1.65	3.07	5.12	6.3	7.68	14.76	8.39	0.59	0.2	34.8

* Design factor 4:1