



- Quenched and Tempered Alloy Steel.
- At least 25% greater WLL than traditional G80 products.
- Manufactured in accordance with EN 1677- 1 and ASTM A952/ A952M.
- Certified by DGUV GS-OA-15-05
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Design Factor 4:1.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Suitable for use with both Grade 80 and Grade 100 chain.



Repair kit available
for maintenance.

G-100 Connecting Link

Item No.	For Grade 100 Chain	WLL tonnes*	Dimensions (mm)				N.W.
	mm		A	B	D	K	kg
X-015-06	6	1.4	15	18	7	45	0.08
X-015-07	7, 8	2.5	18	25	9	59	0.2
X-015-10	10	4.0	25	28	11	69	0.3
X-015-13	13	6.7	30	38	16	92	0.7
X-015-16	16	10.0	36	41	19	101	1.2
X-015-20	20	16.0	42	50	23	122	2.1
X-015-22	22	19.0	49	63	24	152	3.5
X-015-26	26	26.5	55	66	30	162	4.8
X-015-32	32	40.0	69	85	36	203	9.0

★ Design factor 4:1 proof tested and certified.