



Brache piatte in poliestere a doppio strato a norma EN 1492-1
Double layers polyester sling in according to EN 1492-1 standard

Fattore modale
Design factor

Codice Code	Larghezza Width	Lunghezza asole Eyes length	Portata (CMU) (kg) Capacity (WLL) (kg)				
							
			1	2	1,4	1	0,8
	mm	mm	kg	kg	kg	kg	kg
ADS 50	50	200	1000	2000	1400	1000	800
ADS 60	60	270	2000	4000	2800	2000	1600
ADS 90	90	270	3000	6000	4200	3000	2400
ADS 120	120	300	4000	8000	5600	4000	3200
ADS 150	150	400	5000	10000	7000	5000	4000
ADS 180	180	500	6000	12000	8400	6000	4800
ADS 240	240	500	8000	16000	11200	8000	6400
ADS 300	300	600	10000	20000	14000	10000	8000



Descrizione

Brache in Poliestere ad alta tenacità, a singolo o doppio strato, corredate di asole piatte rinforzate

Condizioni di impiego

Fattore di rendimento della portata in funzione della temperatura
CMU/ WLL 100%: -40° C < t ≤ +100° C

Materiale

100% Poliestere ad elevata tenacità

Coefficiente di sicurezza

7:1

Norma di riferimento

EN 1492.1

Certificazione del prodotto

Dichiarazione di conformità "CE" EN 10204 in accordo alla EN 1492.1

*Su richiesta Certificazione e/o collaudo con ente di classifica "IACS" quali RINA - LLOYD'S REGISTER OF SHIPPING - DNV - GERMANISHER LLOYD ed altri

Description

Single or Double layers high tenacity polyester sling with reinforced flat eyes

Use Instructions

Possible reductions of rated load capacity due to temperature exposure cMU/wEE
100% -40°+100°C

Material

100% High tenacity polyester

Safety Factor

7:1

Standard

EN 1492.1

Product Certificate:

"EC" Declaration of conformity EN 10204 acc to EN 1492.1

*Upon request Test certificate issue from "IACS" member such RINA - LLOYD'S REGISTER OF SHIPPING - DNV - GERMANISHER LLOYD and others